

GSM 4/8 Ports Analog Gateway

WT- 244/248



WITURA

WITURA CORPORATION SDN BHD

FEATURES:

- 4 or 8 Voice channels are individually connected with 4 or 8 ports of GSM brand new industrial GSM modules.
- LED GSM status display
- High gain external antenna with 3m cable for optimal signal strength
- Quick call set up and release/echo cancellation
- Individual Channel power supply for easy card replacement
- Thunderstorm and lightning protection
- Set up or cancel call diverting
- Provide accurate anti-polarity signal

- Analog Channel Bank/ SIM Bank
- enables you to quickly achieve the GSM cell telephone communication just via simple operations of wired telephone

Technical Specifications:

- Antenna interface level: 900/1800/1900Mhz, 850/900/1800/1900Mhz
- Dimensions: 500 x 100x 300mm (3U)
- SIM Card: It support 3VG-SIM Card
- Phone Interface: Supply main and assist double frequency interface (RJ-11 Phone Interface)
- Hanging Voltage: 45V
- Picking Off Voltage: 30mA/ 41mA
- Dialing Tone Frequency: 450Hz
- Antenna interface: Antenna Amplifying >4.5DB
- Product Shell: Steel

Operation Circumstance:

- Operation Temperature: -10°C ~ 60°C
- Storage Temperature: -20°C ~ 70°C
- Environment noise: <60DB'
- Transmitting Power: 2W
- Sensitivity: <-104Dbm
- Antenna Amplifying: >1.5db
- Dialing frequency: 450Hz
- Hanging Voltage: 45V
- Picking current: 30mA/41mA
- Power input: 85-240V